ROSS Infrared Lighting Fixture 10W



























General Application Areas






Imaging Systems


ANPR

General Information

The Infrared LED Floodlight is an LED-based lighting device used to support imaging systems. Its energy efficient infrared light has optimized wavelength for night vision. The luminaire body is designed to operate in outdoor conditions. It has a 10° light angle for speed detection, license plate reading and other highway detection systems. Available in 10°, 25°, 40° and 60° for different applications.

Optical Beam Angles





40°

60°

ROSS Infrared Lighting Fixture 10W



Technical Specifications

Body: Aluminum ExtrusionColor Options: 9006 Matte, AnodizedIP Protection Class: IP66 – IP67 (Optional)Front Cover: Tempered Glass

Light Source : LED
Lens : PMMA

Test Standards :EN 60598-1, EN 60529, LM 79-18EN 60598-2-5, IEC TR 62778

Optical and Electrical Properties

Power	10 W	Total Harmonic Distortion	<%20
Wavelength	850 nm	Power Factor	>0,9
Infrared Emission	2.84 W	Warranty Period	3 Years
Light Angle	10°, 25°, 40°, 60°	Weight	1 kg
Input Voltage	220 -240 VAC / 12-24V DC (ops.)	Dimensions	188x142x65 mm
Throttling Options:	1-10V, TRIAC, DALI		

Other Features

Operating Temperature	-25°/+55°C	CE Marking	Yes
Impact Resistance Class	IK 08 – IK 10 (Optional)	RoHS Compliance:	Yes
Lifetime	≥30,000 Hours		

Features

- Ideal for License Plate Recognition Systems.
- Extra Long Life with Very Low Maintenance.
- IP66 Enclosure for Outdoor Installation.
- Compact with integrated LED Light Source.
- The pulse range is adjustable between 1.6K~30KHz.
- Independent or External trigger
- Support synchronized with video camera (NTSC&PAL)
- Super long range up to 30 m.

