



Whiskey Distillery



Hydrogen Fuelled Vessel



Pharmaceuticals

SPARTAN

Hazardous Area LED Lighting

Versatile & Flexible

Rugged & Durable

Easy to Maintain



NEW

Recess Plank

(Zone 1/21 | Zone 2/22)


Variants: 275x800*, 275x1400*

Lumen Outputs: 3,079lm & 6,158lm

Power: 23W & 46W

Colour Temp: 6500K (others available)

IP rating: IP65



NEW

Recess Modular

(Zone 1/21 | Zone 2/22)

Variants: 600x600*, 300x1200*, 600x1200*

Lumen Outputs: 3,079lm, 6,158lm & 12,316lm

Power: 23W, 46W & 92W

Colour Temp: 6500K (others available)

IP rating: IP65



Linear

(Zone 1/21 | Zone 2/22)

Variants: WL84* & WL168*

Lumen Outputs: 3,065lm & 6,130lm

Power: 24W & 49W

Colour Temp: 6500K standard

IP rating: IP66 & IP67



MP Flood & Bay

(Zone 1/21 | Zone 2/22)

Variants: 5K*, 7.5K*, 10K*, 12.5K*, 15K*

Lumen Outputs: 4,792lm, 7,132lm, 9,585lm, 11,981lm, 14,263lm

Power: 40W, 60W, 80W, 100W, 120W

Colour Temp: 5700K

IP rating: IP66 & IP67



Note: This information on this leaflet is for Zone 1 only | *Emergency Options Available

Raytec Global: +44 (0) 01670 520055 • sales@raytecltd.com
Raytec Americas: +1 613 270 9990 • ussales@raytecltd.com

rayTEC[®]
www.raytecltd.com



On Shore Rig



Distillery



Off Shore Rig

FL & BL Flood (Zone 1/21 | Zone 2/22)



Variants: FL24*, FL48* & BL24*
Lumen Outputs: 2,500lm, 4,250lm, 8,450lm, 16,900lm
Power: 20W, 34W, 68W, 136W
Colour Temp: 6000K
IP rating: IP66 & IP67



HP Flood & Bay (Zone 1/21 | Zone 2/22)

Variants: 20K, 25K, 30K
Lumen Outputs: 19,423lm, 24,278lm, 29,134lm
Power: 200W, 250W, 300W
Colour Temp: 5700K
IP rating: IP66



Bulkhead (Zone 1/21 | Zone 2/22)



Variants: BL24* & BL24-HO*
Lumen Outputs: Up to 2,500lm & Up to 4,250lm
Power: 20W & 34W
Colour Temp: 6500K standard
IP rating: IP66 & IP67



Linear High Output (Zone 1/21 | Zone 2/22)

Variants: WL84-HO* & WL168-HO
Lumen Outputs: 6,130 & 12,260lm
Power: 48W & 96W
Colour Temp: 6500K standard
IP rating: IP66 & IP67



Street (Zone 1/21 | Zone 2/22)



Variant: SL96
Lumen Output: Up to 6,770lm
Power: 53W
Colour Temp: 4000K
IP rating: IP66



Note: This information on this leaflet is for Zone 1 only | *Emergency Options Available

Raytec Global: +44 (0) 01670 520055 • sales@raytecltd.com
Raytec Americas: +1 613 270 9990 • ussales@raytecltd.com

rayTEC[®]
 www.raytecltd.com